



Bright Cold Sized Bar 304S11 BS970 Part 3 1991

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
1/8"	0.055	h9	3-3.2 mtrs	12mm	0.888	h9	3-3.2 mtrs
3mm	0.062	h9	3-3.2 mtrs	1/2"	0.994	h9	3-3.2 mtrs
5/32"	0.095	h9	3-3.2 mtrs	14mm	1.21	h9	3-3.2 mtrs
4mm	0.099	h9	3-3.2 mtrs	9/16"	1.26	h9	3-3.2 mtrs
3/16"	0.14	h9	3-3.2 mtrs	15mm	1.39	h9	3-3.2 mtrs
5mm	0.154	h9	3-3.2 mtrs	5/8"	1.55	h9	3-3.2 mtrs
6mm	0.222	h9	3-3.2 mtrs	16mm	1.58	h9	3-3.2 mtrs
1/4"	0.248	h9	3-3.2 mtrs	11/16"	1.88	h9	3-3.2 mtrs
5/16"	0.388	h9	3-3.2 mtrs	18mm	2	h9	3-3.2 mtrs
8mm	0.395	h9	3-3.2 mtrs	3/4"	2.24	h9	3-3.2 mtrs
9mm	0.499	h9	3-3.2 mtrs	20mm	2.47	h9	3-3.2 mtrs
3/8"	0.559	h9	3-3.2 mtrs	7/8"	3.04	h9	3-3.2 mtrs
10mm	0.617	h9	3-3.2 mtrs	24mm	3.55	h9	3-3.2 mtrs
7/16"	0.761	h9	3-3.2 mtrs				

Bright Peeled/Reeled Bar EN 10088-3 1.4307 (304S11 BS970 Part 3 1991)

25mm	3.871	h9	3-3.2 mtrs	1.3/4"	12.179	h9	3-3.2 mtrs
1"	3.97	h9	3-3.2 mtrs	45mm	12.555	h9	3-3.2 mtrs
26mm	4.17	h9	3-3.2 mtrs	1.7/8"	13.977	h9	3-3.2 mtrs
27mm	4.49	h9	3-3.2 mtrs	50mm	15.414	h9	3-3.2 mtrs
1.1/8"	5.033	h9	3-3.2 mtrs	2"	15.906	h9	3-3.2 mtrs
30mm	5.548	h9	3-3.2 mtrs	2.1/8"	17.963	h9	3-3.2 mtrs
1.1/4"	6.346	h9	3-3.2 mtrs	2.1/4"	20.128	h9	3-3.2 mtrs
32mm	6.457	h9	3-3.2 mtrs	60mm	22.205	h9	3-3.2 mtrs
1.3/8"	7.513	h9	3-3.2 mtrs	2.3/8"	22.435	h9	3-3.2 mtrs
35mm	7.55	h9	3-3.2 mtrs	2.1/2"	24.856	h9	3-3.2 mtrs
36mm	7.999	h9	3-3.2 mtrs	2.5/8"	27.409	h9	3-3.2 mtrs
1.1/2"	8.951	h9	3-3.2 mtrs	2.3/4"	30.083	h9	3-3.2 mtrs
40mm	9.872	h9	3-3.2 mtrs	75mm	34.68	h9	3-3.2 mtrs
1.5/8"	10.449	h9	3-3.2 mtrs	3"	35.762	h9	3-3.2 mtrs